

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
540/65R34	152D	TL	W16L W18L	550 21.7	1566 61.7	717 28	4659 183.4	0.8	2150	2220	2050	1960	1870	1	3180	2900
								12	4740	4890	4520	4320	4120	15	7000	6390
								1	2450	2520	2330	2240	2130	1.3	3620	3300
								15	5400	5550	5130	4930	4690	18	7970	7270
								1.3	2850	2940	2720	2600	2480	1.6	4220	3840
								19	6280	6480	5990	5730	5460	24	9300	8460
								2.4	4080	4210	3890	3730	3550	3	6040	5500
								35	8990	9270	8570	8220	7820	44	13300	12110

All tires confirms ETRTO T&RA & STRO standards