

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
440/65R28	138D	TL	W13 W14L W15L	441	1283	587	3819	1.8	2290	2360	2180	2090	1990	2.3	3380	3080
								26	5040	5200	4800	4600	4380	33	7440	6780
								2	2440	2510	2320	2230	2120	2.5	3600	3290
								29	5370	5530	5110	4910	4670	36	7930	7250
								2.2	2580	2650	2450	2350	2240	2.8	3810	3470
								32	5680	5840	5400	5180	4930	40	8390	7640
								2.4	2710	2800	2580	2480	2360	3	4010	3660
								35	5970	6170	5680	5460	5200	44	8830	8060