

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph									
				SW	OD				Non cyclic operation				Cyclic operation					
				mm	mm				Static	25	40	50	65	bar	10	15		
				in	in				16	25	31	40	psi	6	9			
540/65R24	140D	TL	W16L W18L	550	1312	590	3860	0.8	1920	1980	1830	1750	1670	1	2840	2590		
				21.7	51.7			23	152	12	4230	4360	4030	3850	3680	15	6260	5700
										1	2190	2250	2080	2000	1900	1.25	3230	2950
										15	4820	4960	4580	4410	4190	18	7110	6500
										1.3	2540	2620	2420	2320	2210	263	3760	3430
										19	5590	5770	5330	5110	4870	3811	8280	7560
										1.6	2880	2960	2740	2630	2500	2	4250	3880
										23	6340	6520	6040	5790	5510	29	9360	8550

All tires confirms ETRTO T&RA & STRO standards