

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

| Size | LI/SS | Type | Rim | Unloaded dimension | | Loaded Static Radius | Rolling Circumference | Infl.Press | Recommend load, kg (lbs) Speed, km/h (mph) | | | | | | | | |
|---------------|-------|------|---------------------|--------------------|-------|----------------------|-----------------------|------------|---|----------------------|------|------|------|------------------|------|------|------|
| | | | | SW | OD | | | | Field Operation | Non cyclic operation | | | | Cyclic operation | | | |
| | | | | mm/in | mm/in | | | | | 25 | 40 | 50 | 65 | bar | 10 | 15 | |
| 440/ 65R24 | 135D | TL | W13 W14L W15L | 441 | 1182 | 540 | 3565 | bar | 1370 | 1410 | 1300 | 1250 | 1190 | 1 | 2020 | 1840 | |
| | | | | | | | | psi | 12 | 3020 | 3110 | 2860 | 2750 | 2620 | 15 | 4450 | 4050 |
| | | | | | | | | | 1.2 | 1670 | 1720 | 1590 | 1520 | 1450 | 1.5 | 2470 | 2250 |
| | | | | | | | | | 1.7 | 3680 | 3790 | 3500 | 3350 | 3190 | 2.2 | 5440 | 4960 |
| | | | | | | | | | 2.0 | 2250 | 2320 | 2150 | 2060 | 1960 | 2.5 | 3330 | 3040 |
| | | | | | | | | | 2.9 | 4960 | 5110 | 4740 | 4540 | 4320 | 3.6 | 7330 | 6700 |
| | | | | | | | | | 2.4 | 2510 | 2580 | 2390 | 2290 | 2180 | 3 | 3710 | 3380 |
| | | | | | | | | | 3.5 | 5530 | 5680 | 5260 | 5040 | 4800 | 4.4 | 8170 | 7440 |

All tires confirms ETRTO T&RA & STRO standards