

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
480/ 65R24	140D	TL	W15L W14L	480	1234	588	3644	bar	1590	1640	1510	1450	1380	1	2350	2140
								psi	3500	3610	3330	3190	3040	15	5180	4710
								1.2	2000	2060	1910	1830	1740	1.5	2960	2700
								17	4410	4540	4210	4030	3830	22	6520	5950
								2.0	2590	2670	2460	2360	2250	2.50	3830	3490
								29	5700	5880	5420	5200	4960	36	8440	7690
								2.4	2880	2960	2740	2630	2500	3	4250	3880
								35	6340	6520	6040	5790	5510	44	9360	8550

All tires confirms ETRTO T&RA & STRO standards