

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph)							
				SW	OD				Non cyclic operation				Cyclic operation			
									Static		Dynamic		bar		psi	
				mm/in	mm/in				25	40	50	65	bar	10	15	psi
540/65R28	149D	TL	W16L W18L	550 21.7	1413 55.6	640 25.2	4178 164.5	bar	Recommend load, kg (lbs)							
								1.4	2730	2810	2600	2490	2370	1.75	4030	3670
								20	6010	6190	5730	5480	5220	25	8880	8080
								1.6	2940	3030	2800	2690	2560	2	4350	3970
								23	6480	6670	6170	5930	5640	29	9580	8740
								2	3360	3460	3200	3070	2920	2.5	4960	4530
								29	7400	7620	7050	6760	6430	36	10930	9980
								2.4	3740	3850	3560	3410	3250	3	5530	5040
								35	8240	8480	7840	7510	7160	44	12180	11100

All tires confirms ETRTO T&RA & STRO standards