

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
480/70R28	140 A8/B	TL	W14L W15L W16L	490	1421 55.9	643	4200	0.8	3840	2510	2050	1790	1670	1670
								12	8460	5530	4520	3940	3680	3680
								1	4370	2850	2340	2030	1900	1900
								15	9630	6280	5150	4470	4190	4190
								1.3	5080	3320	2720	2360	2210	2210
								19	11190	7310	5990	5200	4870	4870
								1.6	5750	3750	3080	2680	2500	2500
								23	12670	8260	6780	5900	5510	5510

All tires confirms ETRTO T&RA & STRO standards