

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
380/70R28	127 A8/B	TL	W13 W12 W11	380 15	1293 50.9	591 23.3	3846 151.4	0.8	2690	1760	1440	1250	1170	1170
								12	5930	3880	3170	2750	2580	2580
								1	3060	2000	1640	1420	1330	1330
								15	6740	4410	3610	3130	2930	2930
								1.3	3570	2330	1910	1660	1550	1550
								19	7860	5130	4210	3660	3410	3410
								1.6	4030	2630	2150	1870	1750	1750
								23	8880	5790	4740	4120	3850	3850