

FARMAX R70

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance

FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	RIm	Unloaded Dimension					Speed kmph /mph					
				sw	OD mm	SLR mm	RC mm	Infl.Press	Static	10	20	30	40	50
										6	12	19	25	31
				mm				bar	Recommend load kg /lbs					
				in	in	in	in	psi	Tiocommena loau kg / lbs					
360/70R28	125 A8/B	TL	W12 W11 W10	360 14.2	1251 49.3	574 22.6	3730 146.9	0.8	2530	1650	1350	1180	1100	1100
								12	5570	3630	2970	2600	2420	2420
								1	2880	1880	1540	1340	1250	1250
								15	6340	4140	3390	2950	2750	2750
								1.3	3360	2190	1800	1560	1460	1460
								19	7400	4820	3960	3440	3220	3220
								1.6	3800	2480	2030	1770	1650	1650
								23	8370	5460	4470	3900	3630	3630

All tires confirms ETRTO T&RA & STRO standards