

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
580/70R38	155A8/B	TL	W18L	577 22.72	1827 71.93	832 32.7	5420 213.4	0.8	5930	3870	3170	2760	2580	2580
								12	13060	8520	6980	6080	5680	5680
								1	6760	4410	3620	3150	2940	2940
								15	14890	9710	7970	6940	6480	6480
								1.3	7890	5150	4220	3670	3430	3430
								19	17380	11340	9300	8080	7560	7560
								1.6	8910	5810	4770	4150	3875	3875
								23	19630	12800	10510	9140	8540	8540

All tires confirms ETRTO T&RA & STRO standards