

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)						
			SW	OD				Field	10	25	30	40	50	65
			mm/in	mm/in					6	16	19	25	31	40
380/90R46 (14.9 R 46)	159D/162A8	W11	380 15	1852 72.9	864 34	5466 215.2	bar	maximum Load, kg (lbs)						
							psi							
							3.4	4580	5970	4720	4360	4180	3980	3620
							49	10090	13150	10400	9600	9210	8770	7970
							3.6	4740	6180	4880	4510	4330	4120	3750
							52	10440	13610	10750	9930	9540	9070	8260
							3.8	4890	6380	5040	4650	4460	4250	3870
							55	10770	14050	11100	10240	9820	9360	8520
4	5030	6560	5180	4750	4590	4375	3980							
58	11080	14450	11410	10472	10110	9640	8770							

All tires confirms ETRTO T&RA & STRO standards