

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg /lbs						
230/95R48	136D/139A8	TL	W7 W8	228 9	1657 65	785 31	5049 199	2.8	2090	2730	2160	1990	1910	1820	-
								41	4600	6010	4760	4380	4210	4010	-
								3.2	2270	2960	2330	2160	2070	1970	-
								46	5000	6520	5130	4760	4560	4340	-
								3.6	2430	3170	2500	2310	2220	2110	-
								52	5350	6980	5510	5090	4890	4650	-
								4	2580	3360	2650	2450	2350	2240	-
								58	5680	7400	5840	5400	5180	4930	-