

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

| Size | LI/SS | Type | Rim | Unloaded Dimension | | SLR | RC | Infl. Press | Speed kmph / mph | | | | | | |
|-----------|-------------|------|----------|--------------------|--------------|-------------|---------------|-------------|------------------|----------|----------|------------|------|------|------|
| | | | | SW | OD | | | | Field | 10 | 25 | 40 | 50 | 65 | 70 |
| | | | | mm in | mm in | | | | | mm in | mm in | bar psi | 6 | 16 | 25 |
| 230/95R32 | 128D/ 131A8 | TL | W7 W8 | 228 9 | 1251 49.3 | 588 23.1 | 3808 149.9 | 2.8 | 1680 | 2190 | 1730 | 1600 | 1530 | 1460 | 1330 |
| | | | | | | | | 41 | 3700 | 4820 | 3810 | 3520 | 3370 | 3220 | 2930 |
| | | | | | | | | 3.6 | 1940 | 2540 | 2000 | 1850 | 1770 | 1690 | 1540 |
| | | | | | | | | 52 | 4270 | 5590 | 4410 | 4070 | 3900 | 3720 | 3390 |
| | | | | | | | | 4 | 2070 | 2700 | 2130 | 1970 | 1890 | 1800 | 1640 |
| 58 | 4560 | 5950 | 4690 | 4340 | 4160 | 3960 | 3610 | | | | | | | | |

All tires confirms ETRTO T&RA & STRO standards