

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg / lbs						
320/90R42	144D/ 147A8	TL	W9 W10 W11	319	1643	764	4950	2.8	2770	3620	2860	2640	2530	2410	2190
								41	6100	7970	6300	5810	5570	5310	4820
								3.2	3000	3920	3090	2860	2740	2610	2380
								46	6610	8630	6810	6300	6040	5750	5240
								3.6	3220	4200	3320	3070	2940	2800	2550
								52	7090	9250	7310	6760	6480	6170	5620

All tires confirms ETRTO T&RA & STRO standards