

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm in	mm in					mm in	mm in	bar psi	6	16	25
270/95R44 (11.2R44)	140D/ 143A8	TL	W8 W9 W10	275 10.8	1632 64.3	765 30.1	4948 194.8	2.8	2330	3050	2410	2220	2130	2030	1850
								41	5130	6720	5310	4890	4690	4470	4070
								3.6	2700	3530	2780	2570	2470	2350	2140
								52	5950	7780	6120	5660	5440	5180	4710
								4	2880	3750	2960	2740	2630	2500	2280
58	6340	8260	6520	6040	5790	5510	5020								

All tires confirms ETRTO T&RA & STRO standards