

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field						
				mm	mm				6	16	25	31	40	50	
				in	in				in	in	in	in	in	in	
300/95R46 (12.4 R 46)	148D/151A8	TL	W9 W10	300 11.8	1738 68.4	817 32.2	5155 203	bar	2690	3510	2770	2560	2460	2340	2130
								psi	5930	7730	6100	5640	5420	5150	4690
								2.8	2940	3840	3030	2800	2690	2560	2330
								4.1	6480	8460	6670	6170	5930	5640	5130
								3.6	3400	4440	3510	3240	3110	2960	2690
								5.2	7490	9780	7730	7140	6850	6520	5930
								4	3620	4730	3730	3450	3310	3150	2870
								5.8	7970	10420	8220	7600	7290	6940	6320