

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
			SW	OD				Static	10	20	30	40	50
			mm/in	mm/in					6	12	19	25	31
250/85R20	116A8/B	W8 W7 W9	250 9.84	933 36.73	424 16.71	2755 108.5	bar	maximum Load, kg (lbs)					
							psi	2440	1590	1300	1130	1060	1060
							1.8	5370	3500	2860	2490	2330	2330
							2	2600	1700	1390	1210	1130	1130
							2.2	5730	3740	3060	2670	2490	2490
							2.4	2740	1790	1460	1270	1190	1190
							32	6040	3940	3220	2800	2620	2620
							2.4	2880	1880	1540	1340	1250	1250
35	6340	4140	3390	2950	2750	2750							

All tires confirms ETRTO T&RA & STRO standards