

FARMAX HPT



FEATURE

- Tilted lug tip

BENEFIT

- Reduced vibration

FEATURE

- Increased lug width

BENEFIT

- Provides longer service life

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Wide tread width

BENEFIT

- Lower Compaction


FEATURE

- Rounder shoulder

BENEFIT

- Reduced soil disturbance

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Tractor application						
		mm/in	mm/in					Field Operation	10	20	30	40	50	65
650/85R38	DW23B, DW21B, DW20B	675 26.6	2071 81.5	947 37	6181 243	173D/ 176A8	1.0	4470	5840	4780	4470	4260	4080	3890
							15	9850	12860	10530	9850	9380	8990	8570
							1.4	5450	7110	5830	5450	5190	4980	4740
							20	12000	15660	12840	12000	11430	10970	10440
							2.0	6720	8760	7180	6720	6390	6130	5840
							29	14800	19300	15810	14800	14070	13500	12860
							2.4	7480	9750	8400	7480	7120	6830	6500
							35	16480	21480	18500	16480	15680	15040	14320