

FARMAX R90

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph) maximum Load, kg (lbs)									
				SW	OD				Field	10	25	30	40	50				
				mm/in	mm/in					6	16	19	25	31				
420/90R30	147 A8/B	TL	DW13 W14L	436	1518	684 26.92	4483 176.5	bar	5980	3900	3200	2780	2600	2600				
				psi														
				1.8	6350			4140							3390	2950	2760	2760
				2	13990			9120							7470	6500	6080	6080
				2.2	6720			4380							3590	3120	2920	2920
				32	14800			9650							7910	6870	6430	6430
				2.4	7070			4610							3780	3290	3075	3080
				35	15570			10150							8330	7250	6770	6780