

# FARMAX R80

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm	mm					MIXED APPLICATION						
		in	in					Static	10	30	40	50	65	
420/80R46	W13 W12	418 16.5	1840 72.4	853 33.6	5607 220.8	159D 162A8	2.4	7910	5160	3960	3770	3610	3440	
							35	17420	11370	8720	8300	7950	7580	
							2.6	8300	5420	4150	3950	3790	3610	
							38	18280	11940	9140	8700	8350	7950	
							2.8	8670	5660	4340	4130	3960	3770	
							41	19100	12470	9560	9100	8720	8300	
								3	9040	5900	4520	4300	4130	3930
								44	19910	13000	9960	9470	9100	8660
								3.2	9380	6120	4690	4470	4280	4080
								46	20660	13480	10330	9850	9430	8990
								3.6	10060	6560	5030	4790	4590	4375
								52	22160	14450	11080	10550	10110	9640