

FARMAX R80

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load Index	Recommended load, kg (lbs)						
		SW	OD				Infl. press.	Speed, km/h (mph)					
								bar	MIXED APPLICATION				
		mm	mm				mm		mm	Speed	Static	10	30
in	in	in	in	Symbol	psi								
420/80R46	W13	418	1840	853	5607	151D	0.8	4160	2720	2080	1980	1900	1810
							12	9160	5990	4580	4360	4190	3990
	1.2						5290	3450	2650	2520	2420	2300	
	1.7						11650	7600	5840	5550	5330	5070	
	1.6						6260	4080	3130	2980	2860	2720	
	23						13790	8990	6890	6560	6300	5990	
	1.8						6690	4370	3350	3190	3060	2910	
	26						14740	9630	7380	7030	6740	6410	
	2						7130	4650	3570	3390	3260	3100	
	29						15700	10240	7860	7470	7180	6830	
	2.4						7940	5180	3970	3780	3620	3450	
	35						17490	11410	8740	8330	7970	7600	

All tires confirms ETRTO T&RA & STRO standards