

YIELDMAX



FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability

FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning


FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance

MACHINERY



Harvester

*Lower Compaction, Higher Traction and Better Roadability

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)						Cyclic operation (CHO)	
								MIXED APPLICATION							
								bar	10	20	30	40	50		
mm	mm	mm	mm	Speed Symbol	psi	Static	6	12	19	25	31	6	9		
in	in	in	in												
620/75R26	DW20B DW20L	625 24.6	1610 63.4	775 30.5	4856 191.2	166A8/B	2	8720	5690	4660	4060	3790	3790	6820	6250
							26	19210	12530	10260	8940	8350	8350	15020	13770
							2	9800	6390	5240	4560	4260	4260	7670	7030
							32	21590	14070	11540	10040	9380	9380	16890	15480
							2	10300	6720	5510	4790	4480	4480	8060	7390
							35	22690	14800	12140	10550	9870	9870	17750	16280
							3	11270	7350	6030	5240	4900	4900	8820	8090
							41	24820	16190	13280	11540	10790	10790	19430	17820
							3	11730	7650	6270	5460	5100	5100	9180	8420
							44	25840	16850	13810	12030	11230	11230	20220	18550
							3	12190	7950	6520	5670	5300	5300	9540	8750
							46	26850	17510	14360	12490	11670	11670	21010	19270

All tires confirms ETRTO T&RA & STRO standards