

TYROCK

FEATURE

- Traction pattern

BENEFIT

- Suitable for front wheel of back hoe loader



FEATURE

- Special Industrial tread compound

BENEFIT

- Resistant to tearing & cutting

FEATURE

- Wider lug

BENEFIT

- Engineered to provide excellent traction

FEATURE

- Tough nylon casing

BENEFIT

- High load carrying capacity

MACHINERY



Backhoe Loader

Size	Rim	Inflated tire		Loaded Static Radius	Rolling Circum	PR	Inf.	LOAD CARRYING CAPACITY, KG(lbs)				
		dimension				stars		SPEED, Km/h (mph)				
		SW	OD			Load		Press.	INDUSTRIAL USE			
									CONSTANT LOAD		CYCLIC APPLICATION	
		mm	mm			mm		mm	bar	20	40	20
in	in	in	in	psi	12	25	12	25				
18.4-26	DW16LX26	467 18.39	1425 56.10	671 26.41	4275 168.3	12 156A8	1.8	3600	3300	4060	3300	
							26	7930	7270	8940	7270	
							2	3830	3510	4320	3510	
							29	8440	7730	9520	7730	
							2.2	4040	3710	4560	3710	
							32	8900	8170	10040	8170	
							2.5	4360	4000	4920	4000	
							36	9600	8810	10840	8810	