

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)						
		SW	OD					MIXED APPLICATION					CYCLIC*	
		mm/in	mm/in					10	20	30	40 to 65 25 to 40	70	15	30
IF 650/ 60R34	DW23B	650 25.6	1644 64.7	735 29.6	4855 191.1	159D	bar	10	20	30	40 to 65	70	15	30
							psi	6	12	19	25 to 40	43	9	19
							speed symbol	3710	3150	3040	2920	2660	3360	3200
							0.8	8170	6940	6700	6430	5860	7400	7050
							1.0	4230	3600	3460	3330	3030	3830	3650
							1.5	9320	7930	7620	7330	6670	8440	8040
							1.2	4700	4000	3850	3700	3370	4260	4050
							1.7	10350	8810	8480	8150	7420	9380	8920
1.6	5560	4730	4550	4375	3980	5030	4790							
2.3	12250	10420	10020	9640	8770	11080	10550							

All tires confirms ETRTO T&RA & STRO standards