

FARMAX R85

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in				mm/in	10	20	30	40	50	65
380/85R24	131D / 134A8	TL	W12 W13 W11	385	1260	571	3728	bar							
				15.2	49.6	22.5	146.8	psi	Static	6	12	19	25	31	40
				0.8	2990	1950	1600	1500	1420	1370	1300				
				12	6590	4300	3520	3300	2860	3020	2860				
				1	3400	2220	1820	1700	1620	1550	1480				
				15	7490	4890	4010	3740	3260	3410	3260				
				1.3	3980	2600	2130	1990	1890	1820	1730				
				19	8770	5730	4690	4380	3810	4010	3810				
1.6	4490	2930	2400	2240	2140	2050	1950								
23	9890	6450	5290	4930	4710	4520	4300								