RPG

FARMAX R85

CEAT SPECIALTY

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

FEATURE
- Rounded shoulder

BENEFIT
- Reduced damage to soil and crop

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in	mm/in	mm/in	bar	Static	10	20	30	40	50	65
								psi		6	12	19	25	31	40
380/ 85R28	133D/ 136A8	TL	W12 W13 W11	390 15.4	1357 53.4	620 24.4	4035 158.9	0.8	3150	2060	1690	1580	1500	1440	1370
								12	6940	4540	3720	3480	3020	3170	3020
								1	3590	2340	1920	1790	1710	1640	1560
								15	7910	5150	4230	3940	3440	3610	3440
								1.3	4190	2730	2240	2090	1990	1910	1820
								19	9230	6010	4930	4600	4010	4210	4010
								1.6	4740	3090	2530	2370	2260	2160	2060
								23	10440	6810	5570	5220	4980	4760	4540

All tires confirms ETRTO T&RA & STRO standards