RPG

FARMAX R85

CEAT SPECIALTY

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

FEATURE
- Rounded shoulder

BENEFIT
- Reduced damage to soil and crop

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in	mm/in	mm/in	bar	Static	10	20	30	40	50	65
								psi		6	12	19	25	31	40
420/ 85R30	140D/ 143A8	TL	W15L W14L W13	450 17.7	1476 58.1	673 26.5	4385 172.6	0.8	3840	2510	2050	1920	1830	1750	1670
								12	8460	5530	4520	4230	3680	3850	3680
								1	4370	2850	2340	2190	2080	2000	1900
								15	9630	6280	5150	4820	4190	4410	4190
								1.3	5080	3320	2720	2540	2420	2320	2210
								19	11190	7310	5990	5590	4870	5110	4870
								1.6	5750	3750	3080	2880	2740	2630	2500
								23	12670	8260	6780	6340	6040	5790	5510

All tires confirms ETRTO T&RA & STRO standards