

FARMAX R70

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)							
				SW	OD				Speed, km/h (mph)							
				mm/in	mm/in				mm/in	10	20	30	40	50		
280/70R18	114A8/B	TL	W8 W9 W10	282	849	386	2534	bar psi	Static	6	12	19	25	31		
										0.8	930	760	660	620	620	
										12	3150	2050	1670	1450	1370	1370
										1.4	1980	1290	1060	920	860	860
										20	4360	2840	2330	2030	1890	1890
										2	2440	1590	1300	1130	1060	1060
										29	5370	3500	2860	2490	2330	2330
2.4	2710	1770	1450	1260	1180	1180										
35	5970	3900	3190	2780	2600	2600										