

FARMAX R70

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)							
				SW	OD				Speed, km/h (mph)							
				mm/in	mm/in				mm/in	10	20	30	40	50		
200/70R16	94 A8/B	TL	W6	197	686	316	2069	bar	Static	6	12	19	25	31		
										psi	6	12	19	25	31	
										0.8	810	530	430	370	350	350
										12	1780	1170	950	810	770	770
										1.4	1130	740	600	520	490	490
										20	2490	1630	1320	1150	1080	1080
										2	1380	900	740	640	600	600
29	3040	1980	1630	1410	1320	1320										
2.4	1540	1010	820	720	670	670										
35	3390	2220	1810	1590	1480	1480										