

FARMAX R80

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph)											
				SW	OD				Static	10	20	30	40	50						
				mm/in	mm/in					6	12	19	25	31						
480/80R42	169 A8/B	TL	DW16L	485 19.2	1835 72.2	848 33	5472 216.3	bar	11020	7190	5890	5130	4790	4790						
								psi												
								2.8												
								41							24270	15840	12970	11300	10550	10550
								3.2							11910	7770	6370	5540	5180	5180
								46							26230	17110	14030	12200	11410	11410
								3.6							12770	8330	6830	5940	5550	5550
								52							28130	18350	15040	13080	12220	12220
4	13340	8700	7130	6210	5800	5800														
56	29380	19160	15700	13680	12780	12780														

All tires confirms ETRTO T&RA & STRO standards