

YIELDMAX

FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability



FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning

FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded		Static	Rolling	Load			Recommend load, kg (lbs)					Cyclic operation CHO	
		dimension		Loaded	Circum	Index	Infl.		Speed, km/h (mph)						
		SW	OD	Radius			press.		Constant load						
		mm	mm	mm	mm	Speed	bar	Static	10	20	30	40	50	10	15
		in	in	in	in	Symbol	psi		6	12	19	25	31	6	9
620 75R26 SB*	DW20B, DW20L	625 24.6	1610 63.4	775 30.5	4856 191.2	166A8/B	1.8	8720	5690	4660	4060	3790	3790	6820	6250
							26	19210	12530	10260	8940	8350	8350	15020	13770
							2.2	9800	6390	5240	4560	4260	4260	7670	7030
							32	21590	14070	11540	10040	9380	9380	16890	15480
							2.4	10300	6720	5510	4790	4480	4480	8060	7390
							35	22690	14800	12140	10550	9870	9870	17750	16280
							2.8	11270	7350	6030	5240	4900	4900	8820	8090
							41	24820	16190	13280	11540	10790	10790	19430	17820
							3	11730	7650	6270	5460	5100	5100	9180	8420
							44	25840	16850	13810	12030	11230	11230	20220	18550
							3.2	12190	7950	6520	5670	5300	5300	9540	8750
							46	26850	17510	14360	12490	11670	11670	21010	19270

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards