RPG

# TORQUEMAX

CEAT SPECIALTY

**FEATURE**
- Stepped lug design

**BENEFIT**
- Better Grip

**FEATURE**
- Tilted lug tip

**BENEFIT**
- Lower vibration at high speeds.

**FEATURE**
- Strong & wider lugs

**BENEFIT**
- Provides higher contact area leading to higher life

**FEATURE**
- Wider tread width

**BENEFIT**
- Lower Compaction

**FEATURE**
- Lower lug angle at the shoulder

**BENEFIT**
- Better traction

**FEATURE**
- Rounder shoulder

**BENEFIT**
- Lesser soil/crop damage

**FEATURE**
- Steel belted radial construction

**BENEFIT**
- Protection from Punctures

## MACHINERY



High Powered Tractor

| Size | Rim | Unloaded dimension | | Loaded Static Radius | Rolling Circum-ference | PR Load Index | Infl.Press | maximum Load, kg (lbs) Speed, km/h (mph) | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | SW | OD | | | | | MIXED APPLICATION | | | CYCLIC* |
| | | mm/in | mm/in | mm/in | mm/in | speed | bar | static | Up to 65 | 70 | 10 |
| | | | | | | symbol | psi | | Up to 40 | 43 | 6 |
| VF710 70R42 SB* | DW23B DW24B DW25B | 720 28.3 | 2061 81.1 | 902 35.5 | 6119 241.4 | 185D | 0.8 | 11180 | 4860 | 4420 | 6800 |
| | | | | | | | 12 | 24630 | 10700 | 9740 | 14980 |
| | | | | | | | 1.2 | 14170 | 6160 | 5610 | 8620 |
| | | | | | | | 17 | 31210 | 13570 | 12360 | 18990 |
| | | | | | | | 1.6 | 16770 | 7290 | 6630 | 10210 |
| | | | | | | | 23 | 36940 | 16060 | 14600 | 22490 |
| | | | | | | | 2 | 19110 | 8310 | 7560 | 11630 |
| | | | | | | | 29 | 42090 | 18300 | 16650 | 25620 |
| | | | | | | | 2.4 | 21280 | 9250 | 8420 | 12950 |
| | | | | | | | 35 | 46870 | 20370 | 18550 | 28520 |

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards