RPG

FLOATMAX RT

CEAT SPECIALTY

FEATURE
Directional Lug

BENEFIT
Higher traction, Comfortable ride

FEATURE
Robust Centre Blocks

BENEFIT
Low noise and smooth run on hard surface

FEATURE
Steel belted radial construction

BENEFIT
Protection from Punctures

FEATURE
Rounded Shoulder

BENEFIT
Less damage to soil & crops

FEATURE
Interconnected grooves

BENEFIT
Better self cleaning properties

FEATURE
Flatter Crown width

BENEFIT
Larger footprint, lower compaction

MACHINERY

Trailer

Size	Rim	Unloaded dimension SW mm in	Unloaded dimension OD mm in	Static Loaded Radius mm in	Rolling Circum mm in	Load Index Speed Symbol	Infl. press. bar psi	maximum load, kg (lbs) Speed, km/h (mph) MIXED APPLICATION Static	10 6	30 19	40 25	50 31	65 40
500 60R22.5 SB*	AG16.00	503 19.8	1172 46.1	530 20.9	3500 137.8	155D 155D	1.2	4390	3440	2880	2600	2310	1910
							17	9670	7580	6340	5730	5090	4210
							1.6	5200	4070	3410	3070	2730	2260
							23	11450	8960	7510	6760	6010	4980
							2.4	6600	5170	4330	3900	3470	2870
							35	14540	11390	9540	8590	7640	6320
							2.8	7220	5650	4740	4270	3800	3140
							41	15900	12440	10440	9410	8370	6920
							3.6	8370	6550	5500	4950	4400	3640
							52	18440	14430	12110	10900	9690	8020
							4	8910	6980	5850	5270	4690	3875
							58	19630	15370	12890	11610	10330	8540

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards