

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)							
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		Speed, km/h (mph)							
								bar	Static	MIXED APPLICATION					
										10 6	30 19	40 25	50 31	65 40	
600 50R22.5 FT	AG20.00	611	1172	532	3479	159D	0.8	3930	3080	2580	2330	2070	1710		
							12	8660	6780	5680	5130	4560	3770		
							1.6	5890	4610	3870	3480	3100	2560		
		24.1	46.1	20.9	137.0	159D	23	12970	10150	8520	7670	6830	5640		
							2.4	7480	5850	4910	4420	3930	3250		
							35	16480	12890	10810	9740	8660	7160		
		58	22160	17360	14560	13110	11650	9640	3.2	8830	6910	5800	5220	4650	3840
									46	19450	15220	12780	11500	10240	8460
									4	10060	7880	6610	5950	5290	4375

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards