RPG

TORQUEMAX

CEAT SPECIALTY

FEATURE
- Stepped lug design

BENEFIT
- Better Grip

FEATURE
- Tilted lug tip

BENEFIT
- Lower vibration at high speeds.

FEATURE
- Strong & wider lugs

BENEFIT
- Provides higher contact area leading to higher life

FEATURE
- Wider tread width

BENEFIT
- Lower Compaction

FEATURE
- Lower lug angle at the shoulder

BENEFIT
- Better traction

FEATURE
- Rounder shoulder

BENEFIT
- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
		SW	OD					MIXED APPLICATION			CYCLIC*
		mm/in	mm/in	mm/in	mm/in	speed	bar	static	Up to 65km/h	70	10
						symbol	psi		Up to 40mph	43	6
VF 520/ 85R42	DW18 L	536 21.1	1955 77	863 34	5804 228.5	174D/ 177A8	0.8	7410	3220	2930	4510
							12	16320	7090	6450	9930
							1.2	9380	4080	3710	5710
							17	20660	8990	8170	12580
							1.6	11110	4830	4400	6760
							23	24470	10640	9690	14890
							1.8	11890	5170	4700	7240
							26	26190	11390	10350	15950
							2.8	15410	6700	6100	9380
							41	33940	14760	13440	20660

All tires confirms ETRTO T&RA & STRO standards