

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Infl tire dimension		Loaded Static Radius	Rolling Circumference	Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Field	10 6	25 16	40 25	50 31	65 40	70 43	
320/ 90R46	W10 W9 W11	325 12.8	1744 68.7	817 32.2	5260 207.1	146D/ speed symbol	0.8	1530	2000	1580	1460	1400	1330	1210	
							12	3370	4410	3480	3220	3080	2930	2670	
							1.6	2300	3000	2370	2190	2100	2000	1820	
							23	5070	6610	5220	4820	4630	4410	4010	
							2.4	2910	3800	3000	2770	2660	2530	2300	
							35	6410	8370	6610	6100	5860	5570	5070	
							2.8	3190	4160	3280	3030	2910	2770	2520	
							41	7030	9160	7220	6670	6410	6100	5550	
							3.2	3450	4500	3560	3290	3150	3000	2730	
							46	7600	9910	7840	7250	6940	6610	6010	