

YIELDMAX



FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability

FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning


FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance

MACHINERY



Harvester

Size	Rim	Unloaded		Static	Rolling	Load	Infl. press.	Static	Recommend load, kg (lbs)					Cyclic operation	
		dimension		Loaded	Circum	Index			Speed, km/h (mph)						
		SW	OD	Radius					Constant load						
		mm	mm	mm	mm	Speed			10	20	30	40	50	10	15
in	in	in	in	Symbol	bar	6	12	19	25	31	6	9			
						psi									
800/ 65R32 CHO	DW27B, DW25B	800 31.5	1853 73	830 32.7	5540 218.1	181A8/B	0.8	7640	4980	4080	3550	3320	3320	5980	5480
							12	16830	10970	8990	7820	7310	7310	13170	12070
							1.6	11450	7470	6130	5330	4980	4980	8960	8220
							23	25220	16450	13500	11740	10970	10970	19740	18110
							2	13040	8510	6970	6070	5670	5670	10210	9360
							29	28720	18740	15350	13370	12490	12490	22490	20620
							2.6	15200	9920	8130	7070	6610	6610	11900	10910
							38	33480	21850	17910	15570	14560	14560	26210	24030
							3.8	18980	12380	10150	8830	8250	8250	14850	13610
55	41810	27270	22360	19450	18170	18170	32710	29980							