

FLOATMAX RT

FEATURE
Directional Lug

BENEFIT
Higher traction,
Comfortable ride

FEATURE
Robust Centre Blocks

BENEFIT
Low noise and smooth
run on hard surface

FEATURE
Steel belted radial
construction

BENEFIT
Protection from
Punctures



FEATURE
Rounded Shoulder

BENEFIT
Less damage to
soil & crops


FEATURE
Interconnected
grooves

BENEFIT
Better self cleaning
properties

FEATURE
Flatter Crown width

BENEFIT
Larger footprint,
lower compaction

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW	OD	Radius	mm	Speed		Speed, km/h (mph)					
								MIXED APPLICATION					
		mm	mm	mm	mm	Symbol		Static	10	30	40	50	65
in	in	in	in	in	in	bar	6	19	25	31	40		
710 50R26.5 RT	AG24.00	710	1383	621	4188	172D	0.8	5340	4180	3500	3160	2810	2320
							12	11760	9210	7710	6960	6190	5110
		28.0	54.4	24.4	164.9	172D	1.8	8580	6710	5630	5070	4510	3730
							26	18900	14780	12400	11170	9930	8220
		28.0	54.4	24.4	164.9	172D	2.6	10650	8330	6990	6300	5600	4630
							38	23460	18350	15400	13880	12330	10200
							3.4	12470	9760	8180	7370	6560	5420
							49	27470	21500	18020	16230	14450	11940
28.0	54.4	24.4	164.9	172D	4.4	14490	11340	9510	8570	7620	6300		
					64	31920	24980	20950	18880	16780	13880		

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards