

Size / PR : 17.5-25 16PR
Pattern: Grader XL -G2/L2
Type: Tube Type/ Tubeless



- A sturdy, robust tyre for drive wheel off the road equipment.
- Superior tread and sidewall compounds with weather and ozone resistant properties and a strong nylon casing ensures smooth, trouble free services in the most severe operating conditions.
- Ideal for use in motor graders as well as loaders.

Size	Rim Width in	Flange Height in	Unloaded		Loaded	Rolling	PR	Load Capacity		Load Capacity	
			dimension		Static Radius	Circum		GRADER SERVICE		LOADER SERVICE	
			SW	OD				40kmph / (25mph)		10kmph / (5mph)	
			mm in	mm in				Max Load kgs / (lbs)	Infl. Pressure bar / (psi)	Max Load kgs / (lbs)	Infl. Pressure bar / (psi)
17.5-25	14.00	1.5	445 17.5	1360 53.5	614 24.2	4025 158.5	16	3350 7400	3.0 44.0	7300 16100	4.75 69

All tyres conform to T & RA and ETRTO Standards



CEAT Limited. Bhandup (W), Mumbai 400078. T + 91 22 66823535 (B) 25660301 (F)
 Regd. Office : CEAT Limited. CEAT Mahal, 463, Dr. Annie Besant Road, Worli, Mumbai 400030.
 T + 91 22 24930621 (B) 24938933 (F) www.ceatyres.com

