

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in					static	Up to 65km/h Up to 40mph	70 43	10 6
VF 650/ 65R34*SB	DW23B, DW21B	TL	650	1710	750	5061	170D	0.8	8070	3510	3190	4910
			25.6	67.3	29.5	199.2		12	17780	7730	7030	10810
								1.2	10240	4450	4050	6230
								17	22560	9800	8920	13720
								1.4	11200	4870	4430	6820
								20	24670	10730	9760	15020
								2	13800	6000	5460	8400
								29	30400	13220	12030	18500

* SB - Steel belted Note:- for NRO rim please increase 0.2bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards