

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl. Press	Recommend load, kg (lbs)											
		SW	OD					Speed, km/h (mph)											
		mm/in	mm/in					Field	10	25	40	50	65	70					
						speed symbol	bar psi												
300/95R46 (12.4R46)	W9	300	1738	815	5242	143D/	0.8	1300	1700	1340	1240	1190	1130	1030					
							11.6	2860	3740	2950	2730	2620	2490	2270					
	W10						11.8	68.4	32.1	206.4	146A8	1.6	1960	2550	2010	1860	1790	1700	1550
												23.2	4320	5620	4430	4100	3940	3740	3410
												2.4	2470	3230	2550	2350	2260	2150	1960
												34.8	5440	7110	5620	5180	4980	4740	4320
												3.2	2920	3810	3010	2780	2670	2540	2310
												46.4	6430	8390	6630	6120	5880	5590	5090
												3.6	3130	4090	3230	2970	2860	2725	2480
												52.2	6890	9010	7110	6540	6300	6000	5460

All tires confirms ETRTO T&RA & STRO standards