

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Tractor application							
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar psi	Static	10 6	20 12	30 19
800/70R38	DW27B, DW25B	820 32.3	2085 82.1	931 36.7	6223 245	178D/ 181A8	0.8	9060	5910	4850	4530	4310	4140	3940	
							12	19960	13020	10680	9980	9490	9120	8680	
							1.2	11500	7500	6150	5750	5480	5250	5000	
							17	25330	16520	13550	12670	12070	11560	11010	
							1.6	13620	8880	7280	6810	6480	6220	5920	
							23	30000	19560	16040	15000	14270	13700	13040	
							2	15500	10110	8290	7750	7380	7080	6740	
							29	34140	22270	18260	17070	16260	15590	14850	
							2.4	17250	11250	9690	8630	8210	7880	7500	
35	38000	24780	21340	19010	18080	17360	16520								

All tires confirms ETRTO T&RA & STRO standards