

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Tractor application							
								Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi		6	12	19	25	31	40	
710/75R42	DW23B, DW21B, DW24B	725 28.5	2140 84.3	976 38.4	6387 251.5	181D/ 184A8	0.8	8440	5510	4510	4220	4020	3850	3670	
							12	18590	12140	9930	9300	8850	8480	8080	
							1.2	10700	6980	5720	5350	5090	4880	4650	
							17	23570	15370	12600	11780	11210	10750	10240	
							1.6	12650	8250	6770	6330	6020	5780	5500	
							23	27860	18170	14910	13940	13260	12730	12110	
							2.4	16030	10460	8570	8020	7630	7320	6970	
							35	35310	23040	18880	17670	16810	16120	15350	
3.2	18980	12380	10650	9490	9030	8660	8250								
46	41810	27270	23460	20900	19890	19070	18170								

All tires confirms ETRTO T&RA & STRO standards