

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Tractor application							
								Static	10	20	30	40	50	65	
mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi	6	12	19	25	31	40				
600/70R30	DW18L	610	1602	726	4781	158D 161A8	0.8	5130	3350	2740	2560	2440	2340	2230	
		DW 20L	24	63.1	28.6		188.2	12	11300	7380	6040	5640	5370	5150	4910
	1.2		6510	4250	3480		3250	3100	2970	2830					
	1.7		14340	9360	7670		7160	6830	6540	6230					
	1.8		8260	5390	4420		4130	3930	3770	3590					
	26		18190	11870	9740		9100	8660	8300	7910					
	2		8790	5730	4700		4390	4180	4010	3820					
	29		19360	12620	10350		9670	9210	8830	8410					
	2.4	9780	6380	5230	4890		4650	4460	4250						
35	21540	14050	11520	10770	10240	9820	9360								

All tires confirms ETRTO T&RA & STRO standards