

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
		SW	OD					MIXED APPLICATION			CYCLIC*
		mm/in	mm/in					static	Up to 65km/h Up to 40mph	70 43	10 6
IF 710/ 70R38	DW23B DW25B 28.3	720	1959 77.1	850 33.5	5800 228.3	181A8/B	0.8	9130	3970	3610	5560
							12	20110	8740	7950	12250
							1.2	11570	5030	4580	7040
							17	25480	11080	10090	15510
							1.6	13690	5950	5410	8330
							23	30150	13110	11920	18350
							2.4	17340	7540	6860	10560
							35	38190	16610	15110	23260
							2.8	18980	8250	7510	11550
41	41810	18170	16540	25440							