

YIELDMAX



FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability

FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning


FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance

MACHINERY



Harvester

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)					Cyclic operation	
		SW	OD	Radius	Speed	Speed, km/h (mph)									
		mm	mm	mm	mm	bar			Constant load						
		in	in	in	in	psi			10	20	30	40	50	10	15
620/75R34 CHO	DW20B	620	1794	814	5411	170A8/B	0.8	6120	3990	3270	2850	2660	2660	4790	4390
	12						13480	8790	7200	6280	5860	5860	10550	9670	
	1.6						9180	5990	4910	4270	3990	3990	7180	6580	
	23						20220	13190	10810	9410	8790	8790	15810	14490	
	2						10470	6830	5600	4870	4550	4550	8190	7510	
	29						23060	15040	12330	10730	10020	10020	18040	16540	
	2.6						12210	7970	6530	5680	5310	5310	9560	8760	
	38						26890	17560	14380	12510	11700	11700	21060	19300	
	3.2						13800	9000	7380	6420	6000	6000	10800	9900	
46	30400	19820	16260	14140	13220	13220	23790	21810							