

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF710/ 70R42 CFO	DW23B DW25B	720 28.3	2061 81.1	902 35.5	6119 240.9	185D	0.8	11180	5210	4860	4860	4420	1.6	6800	
							12	24630	11480	10700	10700	9740	23	14980	
							1.2	14170	6600	6160	6160	5610	2	8620	
							17	31210	14540	13570	13570	12360	29	18990	
							1.6	16770	7810	7290	7290	6630	2.4	10210	
							23	36940	17200	16060	16060	14600	35	22490	
							2	19110	8900	8310	8310	7560	2.8	11630	
							29	42090	19600	18300	18300	16650	41	25620	
							2.4	21280	9910	9250	9250	8420	3.2	12950	
							35	46870	21830	20370	20370	18550	46	28520	

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards