

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
IF710/ 75R42 CFO	DW23B	720 28.3	2061 77.1	932 33.5	6125 228.3	179D	0.8	9380	5100	4180	4080	3710	1.6	5710	
									12	20660	11230	9210	8990	8170	23
	1.2								11890	6460	5300	5170	4700	2	7240
	17								26190	14230	11670	11390	10350	29	15950
	1.6								14080	7650	6270	6120	5570	2.4	8570
	23								31010	16850	13810	13480	12270	35	18880
	2								16030	8710	7140	6970	6340	2.8	9760
	29								35310	19190	15730	15350	13960	41	21500
	2.4								17830	9690	7940	7750	7050	3.2	10850
	35								39270	21340	17490	17070	15530	46	23900

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards