

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF600/ 70R30	DW20L DW21L	603 23.7	1602 63.1	692 27.3	4731 186.3	170D	0.8	7270	3390	3160	3160	2880	1.6	4420	
							12	16010	7470	6960	6960	6340	23	9740	
							1.2	9200	4290	4000	4000	3640	2	5600	
							17	20260	9450	8810	8810	8020	29	12330	
							1.6	10880	5070	4730	4730	4300	2.4	6620	
							23	23960	11170	10420	10420	9470	35	14580	
							2	12400	5780	5390	5390	4900	2.8	7550	
							29	27310	12730	11870	11870	10790	41	16630	
							2.4	13800	6430	6000	6000	5460	3.2	8400	
35	30400	14160	13220	13220	12030	46	18500								

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards