

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					static	10	20	25 to 65	70	bar	30	
IF710/ 70R38 CFO	DW23B	720 28.3	1959 77.1	850 33.5	5800 228.3	181A8/B	0.8	9130	4250	4070	3970	3610	1.6	5560	
							12	20110	9360	8960	8740	7950	23	12250	
	1.2						11570	5390	5160	5030	4580	2	7040		
	1.7						25480	11870	11370	11080	10090	29	15510		
	1.6						13690	6380	6100	5950	5410	2.4	8330		
	2.3						30150	14050	13440	13110	11920	35	18350		
	2.4						17340	8080	7730	7540	6860	3.2	10560		
	3.5						38190	17800	17030	16610	15110	46	23260		
	2.8						18980	8840	8460	8250	7510	3.6	11550		
4.1	41810	19470	18630	18170	16540	52	25440								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards